




Date: 2019-11-25

MORRIS

Design: Bogesunds Design Team

Article.....	Morris
Article no.....	1561-
Repeat.....	-
Width (cm).....	150 +/- 2 cm
Weight (g/m ²)	475 +/- 5%
Composition.....	100% Trevira CS
Abrasion ISO 12947-2.....	100 000 rubs (Martindale)
- <i>Change in colour at 3000 rubs</i>	4-5 (Scale 1-5)
Pilling ISO 12945-2.....	4 (Scale 1-5)
Colour fastness:	
- <i>to light</i> ISO 105-B02.....	5-7 (Scale 1-8)
- <i>to rubbing</i> ISO 105-X12.....	Dry 4 / Wet 3-4 (Scale 1-5)
- <i>to perspiration</i> ISO 105-E04.....	Acid 4 / Alkaline 4 (Scale 1-5)
- <i>to water spotting</i> ISO 105-E16..	4-5 (Scale 1-5)
Flame resistance	EN 1021-1 & 2 (20-22 kg/m ³ non fire retardant polyurethane foam) ISO EN 45545-2, R21 (Safety level HL1 and HL2) ECE Regulation 118-03, annex 6, 7 and 8
Care instructions.....	
Country of origin.....	Sweden - some colour nuance can occur between batches. - fulfill Möbelfakta requirements.
  SE/016/006	